

4-Wire Cable Tester

8761NAK/8761NK

Features

- 4-wire measurement Cond. Resistance 1mΩ-52Ω
- Low Resistance Scanning Test 10mΩ-52Ω
- Test pin 512
- Number of test file up to 500 sets
- Open/Short
- Conductance
- AC/DC Hipot Test
- DC insulation
- Support bar code scan and print function

Application

All kinds of wires, connectors and combined products of connectors and wires



CE RS-232 Remote USB Host Print

Accessories / Fixtures


Standard

- Power Cord
- 64P 3KV Cable (AK8600F3)
- Adapter board (FX-000C16)
- Probe

Optional


- PC link software
- Remote control cable
- Calibration Kits (KB-8740K1)
- Multiple DUT Testing Expand Box (F874001)
- Adapter board (FX-000C15)
- Adapter board (FX-000C17)
- FX-000C18
- FX-000C21 (USB Type A)
- FX-000C22 (USB Type C)
- FX-000C27
- Networking Fixture
- D-Sub Foot switch (F760001)

Key Features




Low Resistance Test: Detect the open/short problem on the contact point of the terminal.

B Open/Short Test



Open/Short Test: Make sure the contact of wire work properly.

C Hi-pot Test



Put a stable high voltage on cable to make sure the quality of DUT.

- DC insulation

The result will judge by the rate of insulation resistance. Insulation resistance defect may cause DUT be penetrated or leakage current under high voltage.

- Arc Test

Some high precision product for automobile and military can't accept any arc under high voltage.

Specification

Model Name	8761NAK	8761NK	
AC Output Voltage	100-700V	-	
DC Output Voltage	50-1000V		
Measuring Mode	4-wire		
Test Pin	512		
Safety Hi pot Test	AC Hipot Leakage Current	0.01mA-5mA	
	AC Arcing Detection	1-48	
	DC Hipot Leakage Current	0.1 μ A-1000 μ A	
	DC Arcing Detection	1-48	
	DC Hipot Insulation Resistance	1M Ω -1.2G Ω	
	Hipot Output Accuracy	\pm 5%	
	Hipot Measurement Accuracy	\pm 5%	
	Rated Output	5Vdc	
	Hipot Measurement Time	0.01 sec-60 sec	
	Wire Specifications	Maximum allowable capacitance 5 μ F	
Low Voltage Electrical Test	Cond. Resistance	1m Ω -52 Ω	
	Intermittence Cond. Resistance	1m Ω -52 Ω	
	O/S, Intermittence O/S, Quick Intermittence open circuit	1k Ω -100k Ω	
	Low resistance Scanning	Measurement Range	10m Ω -52 Ω
		Current Signal	10mA
	Single-Side Test	•	
O/S Terminal Judge	•		
Component test	Resistance	Measurement Range	50m Ω -20M Ω
		Level signal	0.5-3V
		Current Signal	10mA
	Capacitance	Measurement Range	10pF-12 μ F
		Level signal	0.3V-1.2V
		Frequency signal	AUTO Gear (Optional) 48Hz/ 480Hz/ 4.8kHz/ 48kHz
Diode	Measurement Range	0-6.8V	
Advanced Functions	Programmable continuous test/ Pin search/ Auto-diagnosis		
Test Scan Mode	Auto, Manual, External Trigger		
Measurement Signal	Low Voltage Measurement Signal		
Built-in Storage	Number of test file up to 500 sets		
Panel	System/ Rapid/ Edit/ Function		
Indicator	Pass/ Fail HV LED red-green indicator lights/ Screen Display/ Sound		

General

Operation	Manual, Auto, Remote Control
Interface	RS-232, USB Host, Print, Remote
Power Supply	Fixed Voltage 115/230 Vac \pm 10%
	Frequency 60/50Hz
Power Consumption	250VA
Display	320*240 dot-matrix
Environment	Temperature: 15 $^{\circ}$ C-35 $^{\circ}$ C, Humidity: RH \leq 70%
Dimension (W*H*D)	435*270*360mm
Weight	18kg